



Princeton

This school lighting combines comfort and light quality to ensure that students in all areas can see the contents on the blackboard clearly, prevent vision issues and assure healthy eyes for the students. It is suitable for hanger rod installation.

Wattage: 30W
 CRI : Ra≥90
 CCT : 5000K
 Beam : 70°
 Finish : Aluminum Oxide
 Material : Aluminum frame, PMMA diffuser
 Driver : Built-in constant current LED driver
 Driver can be ON/OFF, Triac dimming, 0/1-10V dimming or DALI
 IP rating: IP20



Accessories Options



Installation Kit (Rod length: 1000mm / 1500mm)

 CEE1012H-C 30W 5000K EPISTAR	 70° 30W 5000K 2600lm		h(m)	E _{max} (lx)	D(cm)
			1	1782	98.99
			2	445.6	197.97
			3	198.0	296.96
			4	111.4	395.94
			5	71.29	494.93

* IES files are available for downloading from the website; or if needed, contact our sales managers please.

Parameters

LED Module	Driver	CCT	Luminaire Lumen
30W	/	5000K	2600-2800lm

Dimensions

Model	Wattage	Length(L)	Width(W)	Height(H)	Line Art
CEE1012H-C	30W	1180mm	35mm	46mm	

ORDERING INFORMATION :

Example : CEE1012H-C-30W-950-ND-BK10

Model	Wattage	CRI & CCT	Dimming	Accessories
CEE1012H-C	30W	950	ND	BK10
CEE1012H-C	30W	950 Ra ≥ 90 5000K	ND Non Dim TD Triac Dim VD 0/1-10V Dim DD DALI Dim	BK10 Installation Kit (1000mm) BK15 Installation Kit (1500mm) The accessories should be specified separately.

The above listed accessories is NOT compulsory, however could be specified when ordering.