



B Series -3528

This is the IP20 version of B series strip light - the best cost performance option in the light strip portfolio. Selected SMD3528 chips, Ra>90, R9>50, SDCM≤5, and the lighting efficiency is higher than 70lm/W. There are two light color options in the 3000K range as LED strip light in white for effective ambience, and LED strip light in warm white for cozy lighting environment.

Input Voltage : DC 24V
 Wattage : 4W/M
 CRI : Ra≥90
 CCT : 2400K / 2700K / 3000K / 3500K / 4000K / 6400K
 Beam : 120°
 Finish : White
 Material : PCB
 Package : 5M / Roll
 IP rating : IP20

Accessories Options




Parameters

Wattage	LED QTY (pcs/m)	CCT	Luminaire Lumen (lm/m)
4W	60	3000K	260-360lm/m

Dimensions

Model	Wattage (W/M)	Width(W)	Height(H)	Line Art
CEGB3528-50 G3	4W/M	8mm	2.2mm	

CEGB3528-50 G3
 Minimum cutting unit : 6pcs/100mm



Driver Options

Model	Wattage	Non-Dim Driver	Driver Wattage
CEGB3528-50 G3	20W/Roll	CE1.5A-24	36W

- One LED driver can be series connected maximum in 10 meters LED strip light (2 rolls)
 - The LED driver power must be at least 10% more than the total power of the LED strip light.
 - Specific driver model no. pls kindly refer to Page 464-467 CDN Constant Voltage LED Driver.
- * Some of the other branded drivers may available as options, please contact our sales managers if needed.

ORDERING INFORMATION :

Example : CEGB3528-50 G3-60-924-24V-IP20-ND

Model	LED QTY/M	CRI & CCT	Input Voltage	IP Rating	Dimming
CEGB3528-50 G3	60	924	24V	IP20	ND
CEGB3528-50 G3	60	924 Ra ≥ 90 2400K 927 Ra ≥ 90 2700K 930 Ra ≥ 90 3000K 935 Ra ≥ 90 3500K 940 Ra ≥ 90 4000K 964 Ra ≥ 90 6400K	24V	IP20	ND Non Dim TD Triac Dim VD 0/1-10V Dim DD DALI Dim

The above listed accessories is NOT compulsory, however could be specified when ordering.

*Remarks: The specs is subject to change without prior notice.